



Mister Worker[®]
YOUR PROFESSIONAL TOOLS SUPPLIER

CATALOG

SEPTEMBER 2020



STANLEY.

ELECTRONIC DEVICES



DIGITAL MULTIMETER

FEATURES: - Simple to use, compact, robust - AC / DC Voltage 600V - AC / DC Current 10A - Resistance 2M - Battery test function - Resolution 3 1/2 (from zero to 1999) - Hold function - Continuity acoustic signal <30 - 2.4V Diode Measu ...

| | |
|-------|-------------|
| CODE | FMHT82565-0 |
| PRICE | € 29,70 |





INFRARED THERMOMETER

IN BRIEF Stanley STHT0-77365 - For minimal surface scarring and entry into most cavities and areas. 1 m camera wand length. Screen rotation. Water- and dust-proof. DESCRIPTION Easy To Use, Highly Accurate Infrared Thermometer. Compact, Rugged De ...

| | |
|-------|-------------|
| CODE | STHT0-77365 |
| PRICE | € 41,25 |



INSPECTION CAMERA

IN BRIEF Stanley STHT0-77363 - Receiver for rotating lasers. Range of use : 200 m. 2 levels of precision : ± 6 mm and ± 30 mm. IP67 standards. Automatic shutdown. DESCRIPTION For Minimal Surface Scarring And Entry Into Most Cavities And Areas. ...

| | |
|-------|-------------|
| CODE | STHT0-77363 |
| PRICE | € 117,00 |



STANLEY® FATMAX® INSPECTION CAMERA

9mm wide camera head for minimal surface scarring and entry into most cavities and areas Detachable 3.5 inch colour TFT-LCD display 3 times camera zoom Rotating image position enables users to rotate the display to get the best angle possible when vi ...

| | |
|-------|-------------|
| CODE | FMHT0-77421 |
| PRICE | € 222,00 |



MOISTURE METER (2 PCS.)

IN BRIEF Stanley 0-77-030 - Dual measurement scale, LCD display Measures wood moisture from 6% to 44% and building material moisture from 0.2% to 2.0% DESCRIPTION Dual Measurement Scale, Lcd Display With Bar Graph Measures Wood Moisture Fro ...

| | |
|-------|----------|
| CODE | 0-77-030 |
| PRICE | € 70,35 |



S210 FATMAX® DETECTOR

Detects the center of wooden elements up to 25 mm, metal up to 38 mm, live electrical cables up to 50 mm. Led screen Auto calibration: eliminates the possibility of error due to incorrect initial calibration Angle tolerance: reduces the possibility o ...

| | |
|-------|-------------|
| CODE | FMHT77589-0 |
| PRICE | € 25,49 |



S260 FATMAX® DETECTOR

Detects the center of wooden elements up to 25 mm, non-ferrous metal up to 50 mm, ferrous metal up to 76 mm, live electrical cables up to 50 mm. Led screen Auto calibration: eliminates the possibility of error due to incorrect initial calibration Ang ...

| | |
|-------|-------------|
| CODE | FMHT77590-0 |
| PRICE | € 32,00 |



S310 FATMAX® DETECTOR

Detects the center of wooden elements up to 25 mm, non-ferrous metal up to 50 mm, ferrous metal up to 76 mm, live electrical cables up to 50 mm. Backlit LED screen for greater readability thanks to the icons Auto calibration: eliminates the possibli ...

| | |
|-------|-------------|
| CODE | FMHT77591-0 |
| PRICE | € 36,70 |



STUD SENSOR

Material detected: wood, metal, AC. Detection depth: wood stud 19 mm, metal stud 19 mm, AC 50 mm. Stud detection: center read. Contains 2 AAA batteries. Characteristics: center find, angle tolerance, auto calibration. Slim design.

| | |
|-------|-------------|
| CODE | STHT77587-0 |
| PRICE | € 16,49 |





STUD SENSOR

Material detected: wood, metal, AC. Detection depth: wood stud 25 mm, metal stud 39 mm, AC 50 mm. Stud detection: center read. Contains 2 AAA batteries. Characteristics: center find, angle tolerance, auto calibration. Slim design.

| | |
|-------|-------------|
| CODE | STHT77588-0 |
| PRICE | € 18,60 |

